

lightnet

Cubic-P2

Pendant luminaire - Direct/indirect light distribution

Article code: CP2OEL-840H-Q630-K



Illustrations may only be similar and serve as an orientation.

Cubic-P2. LED. Pendant luminaire with minimalist edge of only 5mm. Luminaire body made of high-quality aluminum profile. Surface finish Silver Anodised. Direct/indirect light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Dimmable DALI. LxWxH (square). L=630mm. W=630mm. H=75mm. Cord suspension for parallel installation with power supply cable and ceiling rose (Set).



Pendant length max 1500mm. Power supply: transparent. Ceiling rose: Matching luminaire's surface colour. High-power current. 14530lm. 103W. 13kg. Binning initial <= MacAdam 3. IP20. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,4%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L80B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated

lightnet

Cubic-P2

Pendant luminaire - Direct/indirect light distribution

Article code: CP2OEL-840H-Q630-K



Customer / Project: _____

Note: _____

Productname	Cubic-P2
Lamp	LED
Installation Type	Pendant luminaire
Surface finish	Silver Anodised
Light characteristics	Direct/indirect light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Dimmable (DALI)
Length L/Diameter D (mm)	L=630mm
Width W (mm)	W=630mm
Height H (mm)	H=75mm
Current/Power	High-Power
Luminous Flux	14530lm
Power consumption	103W
Suspension	Parallel susp. (Set)
Ceiling rose colour	Ceiling rose: Matching luminaire`s surface colour
Pendant length (mm)	Pendant length max 1500mm
Degree of protection	IP20
Certification	Prüfzeichen: ENEC
Cable Colour	Power supply: transparent
LED lifetime	L80B10 (tq 25°C) = 50.000h
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	13kg

