

APUS M (787 013)



| Typ Art.-Nr. | APUS M 787 013 |
|--|---|
| Störlichtbogenschutzklasse (Box-Test 4 kA/0,5 s – ein- polig) | APC 1 |
| Lichtbogenenergie (W_{arc} oder W_{LBP}) | 168 kJ |
| Arc Rating – ATPV (Open Arc Test) | 4,1cal / cm ² |
| in Kombination mit DEHNcare ArcFit Indoor | 31cal / cm ² |
| in Kombination mit DEHNcare ArcFit Outdoor | 37cal / cm ² |
| Arc Rating – ELIM (in Kombi- nation mit DEHNcare ArcFit Indoor) | 28cal / cm ² |
| Arc Rating – ELIM (in Kombi- nation mit DEHNcare ArcFit Outdoor) | 34cal / cm ² |
| Normen | IEC 61482-2, EN ISO 11612, EN 1149-5 |
| Material | Baumwolle (50%), Modacryl (39%), Viscose (10%), Antistatika (1%) |
| Flächengewicht | 160g/m ² |
| Größe (International) | M |
| Farbe | blau |
| Gewicht | 306,66 g |
| Zolltarifnummer (Komb. Nomenklatur EU) | 61091000 |
| GTIN (EAN) | 4013364482753 |
| VPE | 1 Stk. |