

Panel mounting socket outlet - flange 75x75, fixing centers 60x60, straight execution




| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 4366 |
| EAN | 4024941043663 |
| Product category | Panel mounting socket outlet, extra-low voltage, straight |
| Current | 32A |
| Number of poles | 2p |
| Poles | 2P |
| Position of earth contact | 12 h |
| Voltage | 40 up to 50V |

| Product description | |
|--------------------------------|--|
| Frequency | 50 and 60Hz |
| Protection degree | IP44 |
| Colour code | gray RAL 7035 |
| Colour of appliance | Hinged lid grey RAL 7035, Enclosure grey RAL 7035 |
| Connection design | with screw terminal |
| Maximum conductor size | 10,0 qmm |
| Cable entry | other |
| Height | 76mm |
| Width | 75mm |
| Depth | 61mm |
| Flange size vertical | 75mm |
| Flange size horizontal | 75mm |
| Drill hole distance vertical | 60mm |
| Drill hole distance horizontal | 60mm |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of polyamide, the contacts are brass nickel plated |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.127 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941043663 |
| Length | 61 mm |
| Width | 75 mm |
| Height | 76 mm |
| Weight | 0.128 kg |
| Volume | 347.7 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941836722 |
| Length | 207 mm |
| Width | 162 mm |
| Height | 142 mm |
| Weight | 1.37 kg |
| Volume | 3,750 ccm |



16 MB 47

| Ampere | 16 | 16 | 32 | 32 | | |
|----------------------------|------|------|------|------|--|--|
| Polzahl | 2 | 3 | 2 | 3 | | |
| a | 75,0 | 75,0 | 75,0 | 75,0 | | |
| b | 75,0 | 75,0 | 75,0 | 75,0 | | |
| c | 60,0 | 60,0 | 60,0 | 60,0 | | |
| d | 60,0 | 60,0 | 60,0 | 60,0 | | |
| e ø | 5,2 | 5,2 | 5,2 | 5,2 | | |
| f | 6,0 | 6,0 | 6,0 | 6,0 | | |
| h | 22,0 | 22,0 | 22,0 | 22,0 | | |
| i | 37,0 | 37,0 | 37,0 | 37,0 | | |
| k | 67,0 | 67,0 | 67,0 | 67,0 | | |
| l ø | 49,0 | 49,0 | 49,0 | 49,0 | | |
| m | 2,0 | 2,0 | 2,0 | 2,0 | | |
| Leiter mm ² min | 4 | 4 | 4 | 4 | | |
| Leiter mm ² max | 10 | 10 | 10 | 10 | | |