



The pendant lamp is an appropriate addition to the OFFICE THREE MOTION standing lamp. As the glare value is under 10, this sophisticated light can be thought of as being almost entirely glare-free. The LEDs directed upwards create room lighting, whilst the LEDs directed downwards emit clearly defined and powerful light onto the work area.

#### Special features

- Very low UGR value
- High luminous flux
- Controlled using DALI 2.0
- Max. suspended mounting 2,500 mm

<b>Housing Material</b>	Aluminium	<b>Pendulum Length max.</b>	2500 mm
<b>Housing Color</b>	White	<b>Working Temperature</b>	-5 to 40 °C
<b>Material of Lens</b>	Plastic	<b>Storage Temperature</b>	-10 to 40 °C
<b>Protection Class</b>	Protection class I/protective grounding	<b>IP Protection Class</b>	IP 20
<b>Rated Input</b>	60 W	<b>Life Time L70 / B50</b>	50000 h
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz	<b>Life Time L80 / B10</b>	50000 h
<b>Power Supply Unit incl.</b>	Yes	<b>Switching Cycles</b>	25000
<b>Connection Type</b>	Clamp	<b>Power Consumption</b>	60 kWh/1000h
<b>Dimmable</b>	Yes	<b>Energy Efficiency Class</b>	E
<b>Control technology</b>	DALI 2 / DT6		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	7000 lm		
<b>Rated Angle of Reflection</b>	115 Degree		
<b>Rated Angle of Reflection 2</b>	55 Degree		
<b>UGR</b>	6		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below		
<b>Length</b>	1179 mm		
<b>Width</b>	64 mm		
<b>Height</b>	35 mm		
<b>Base length</b>	600 mm		
<b>Base width</b>	56.5 mm		
<b>Base height</b>	35 mm		