



<b>Housing Material</b>	Polycarbonate	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Color</b>	Grey	<b>Switching Cycles</b>	20000
<b>Housing Surface</b>	Transparent	<b>Power Consumption</b>	4 kWh/1000h
<b>Colour of Lens</b>	Transparent	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class F.
<b>Functions</b>	Walkable - 5 kN		
<b>Protection Class</b>	Protection class II/protective insulation		
<b>Rated Input</b>	3.7 W		
<b>Rated Input Voltage</b>	220-240 V/AC		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Open cables		
<b>Primary Cable Length</b>	0.3 m		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000 K		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	240 lm		
<b>Luminous Efficiency</b>	64.9 lm/W		
<b>Rated Angle of Reflection</b>	120 Degree		
<b>Length</b>	200 mm		
<b>Width</b>	200 mm		
<b>Height</b>	68 mm		
<b>Installation Depth</b>	68 mm		
<b>Product weight</b>	1171 g		
<b>Working Temperature</b>	-20 to 45 °C		
<b>Storage Temperature</b>	-20 to 60 °C		
<b>IP Protection Class</b>	IP 67		
<b>IK Protection Class</b>	IK10		
<b>Load Force max.</b>	5 kN		