



Housing Material	Die-cast aluminium	Length	100 mm
Housing Color	Black	Width	100 mm
Material of Lens	Plastic	Height	380 mm
Protection Class	Protection class III/safety extra-low voltage	Diameter	115 mm
Operating Mode	Constant voltage	Base length	100 mm
Rated Input	2.2 W	Base width	100 mm
Rated Input Voltage	5 V/DC	Base height	11 mm
Power Supply Unit incl.	No	Product weight	1028 g
Connection Type	Micro-USB	Working Temperature	-20 to 45 °C
Dimmable	Yes	Storage Temperature	-20 to 45 °C
Control technology	Touch-Sensor	IP Protection Class	IP 54
Motion Detector	No	Life Time L70 / B50	30000 h
Accumulator/Battery Operated	Yes		
Rechargeable/battery included	Yes		
Number of Accumulator/Battery	1		
Type of Accumulator/Battery	Li-Ion battery type 18650		
Accumulator/Battery Capacity	4400 mAh		
Accumulator/Battery Voltage	3.7 V/DC		
Accumulator Charging Time	5-7 h		
Accumulator Operating Time	9 h		
Light Source	LED, Light source not changeable		
Lightcolor	Warm white (WW)		
Color Temperature	3000 K		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	154 lm		
Luminous Efficiency	70 lm/W		
Rated Angle of Reflection	106 Degree		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		