



Housing Material	Die-cast aluminium	Diameter	120 mm
Housing Color	Yellow	Product weight	355 g
Material of Lens	Plastic	Working Temperature	-20 to 45 °C
Protection Class	Protection class III/safety extra-low voltage	Storage Temperature	-40 to 60 °C
Operating Mode	Constant voltage	IP Protection Class	IP 54
Rated Input	2.2 W	Life Time L70 / B50	30000 h
Rated Input Voltage	3.7 V/DC	Switching Cycles	15000
Power Supply Unit incl.	No	Power Consumption	3 kWh/1000h
Connection Type	USB type C		
Dimmable	Yes		
Control technology	Touch-Sensor		
Motion Detector	No		
Accumulator/Battery Operated	Yes		
Rechargeable/battery included	Yes		
Number of Accumulator/Battery	1		
Type of Accumulator/Battery	Li-Ion battery type 18650		
Accumulator/Battery Capacity	4400 mAh		
Accumulator/Battery Voltage	3.7 V/DC		
Accumulator Charging Time	5-7 h		
Accumulator Operating Time	12 h		
Light Source	LED, Light source not changeable		
Lightcolor	Warm white (WW)		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	196 lm		
Luminous Efficiency	89.1 lm/W		
Rated Angle of Reflection	47 Degree		
Light Distribution	Asymetric		
Distribution Characteristic 120°	DLS		
Height	30 mm		